

G-4400



Stronger for longer

GARAGA

INDUSTRIAL

The G-4400 Service Station door, 1 3/4 in. thick, is a sturdy and reliable product. It was designed for those who need maximum natural light such as: car dealerships, firestations, bars and restaurants terrace, etc. Available in a wide choice of standard and custom sizes, this door will bring style to your business.

G-4400

Features

- 1 Thickness of the door 1 3/4 in. (44.5 mm).
- 2 Clear Anodized, White or Black pre-painted tubular extrusions.
- 3 Top-to-bottom end extrusion 6 1/4 in. (159 mm) at perimeter.
- 4 Double hinge end extrusion, 6 1/4 in. (159 mm).
- 5 Thickness of tubular extrusions: 0.125 in. (3.2 mm) at hinge fastening points.
- 6 Weatherstripping between sections.
- 7 Bottom panel weatherstripping.
- 8 Rigid vinyl (PVC) pane moulding.
- 9 Center hinge equally spaced.
- 10 Integral reinforcement struts (for doors 14 feet (4267 mm) wide and over).
- 11 Kick proof panel, pre-painted aluminum, choice of 11 colours including anodized, panel only.

Specifications

Door

0.063 in. (1.6 mm) thick tubular aluminum extrusion (6063 T5) with a clear anodized or white or black pre-paint finish. Total thickness of 1 3/4 in. (44, 5 mm).

Window selection

We offer a wide choice of thermo, clear or tinted panes, acrylic or polycarbonate panes, tempered panes. Contact our customer service to order any other type of window.

Weather tightness

Inset weatherstripping at each door panel intersection and "U" shape TPE (Thermoplastic Elastomer) flexible weatherstripping at the bottom of the door.

1 Please contact our Technical Service for larger sizes and/or option of changing the number of units per section.

Hardware

13 or 14-gauge, 2 inch (51 mm) commercial track (for doors up to 180 kg (396 lbs) or 10 m² (108 sqft)) or 12-gauge, 3 inch (75 mm) industrial tracks. Helicoidal torsion springs. Sturdy galvanized steel hardware suited for the intended use of the door.

Weatherstripping (jambs and lintel):

Aluminum extrusion base weatherstripping double-edge rubber strip or artic vinyl, and rigid PVC screw cover (optional).

Options

Exhaust port 3 in. (76 mm)

Each door is custom built to meet your specifications. We will be able to help you with our expertise and follow up at every stage until the end of your project.

Garaga has established a permanent research program for all of its products. Technical specifications for this door are subject to change without notice.

Available sizes ¹

Widths: from 4 to 18 feet, from 1219 mm to 5486 mm

Heights: from 6 to 14 feet, from 1829 mm to 4267 mm

Custom size to the nearest 1 in. (25.4 mm)

Number of units per section

96 to 111 in. (2 438 to 2 819 mm) – 2

112 to 147 in. (2 845 to 3 734 mm) – 3

148 to 194 in. (3 759 to 4 928 mm) – 4

195 to 216 in. (4 953 to 5 486 mm) – 5



* Integral reinforcement strut



E-mail: info@garaga.com
www.garaga.com

8500, 25th Avenue
 Saint-Georges, QC Canada G6A 1K5
 Tel.: **418.227.9458**



Products manufactured in Canada
 © Garaga Inc. 2012 - All rights reserved

